

Audio signal processing device

The invention relates to an audio signal processing device for speech and music signals.

Although the speech and sound signals come from a certain direction defined by an arrangement of loudspeakers, there is nevertheless a demand that speech and music signals should seem to come from different directions, as perceived by listeners.

To achieve this object, the audio signal processing device according to the invention is provided with signal supply means for supplying speech and music signals over one or several (n) different input channels, separation means for substantially separating the speech and music signals, first converter means for converting the music signals in accordance with a desired virtual spatial widening from which the music signals can be heard through one or several (m) different output channels, and combination means for combining the speech signals with the converted music signals.

It is true for the case in which $n = 2$ and $m = 2$, i.e. for conventional stereo sound reproduction, for example with the use of headphones, that music can be heard with a virtual spatial spread through the use of an audio signal processing device according to the invention, and speech can be equally distributed over the two channels (left and right) as a mono signal, or can be heard through one of the two channels (left or right). The music heard in a wider spatial virtual spread is referred to hereinafter as "widened" music for short. The device according to the invention renders it possible, accordingly, to widen music but not speech, and can be effective both for speech and music signals separately and for the simultaneous reproduction of speech and music.

Since it may be desirable in certain circumstances to have the speech appear from any other direction desired, it is possible furthermore according to the invention that signal direction detection means are present for ascertaining the direction from which the speech signals originate, and second converter means for converting the speech signals in accordance with a desired virtual change in the direction from which the speech signals can be heard, the converted speech signals and the converted music signals being joined together in the combination means.

This measure renders it possible, for example, that speech is still being heard through headphones from the direction of a speaker, whether the latter is stationary or is walking to and fro, or even if several speakers are present who address an auditorium consecutively from different spatial angles. The measures according to the invention may also be important for videoconferencing, where the speech can also be made to originate from the direction of the speaker on a displayed video picture and not from the direction from which image and sound were recorded. It may be especially unpleasant and adversely affect the ease of understanding of speech when the perceived directions of image and sound do not coincide.

The second converter means mentioned above may be provided with one or several additional input channels through which speech and position signals can be supplied from a microphone having position recording means. Speech signals from a further speaker can be put in in this manner and be reproduced as though coming from the direction of this speaker.

The invention further relates to an audio reproduction system provided with an audio signal processing device as described above, and with sound reproduction means for the separate output channels for rendering amplified speech and music signals audible.

The invention also relates to an audiovisual reproduction system provided with an audio signal processing device as described above and to a unit in which a picture screen and sound reproduction means are incorporated.

The invention will now be explained in more detail below with reference to the accompanying drawing, which is a block diagram representing the functions of the audio signal processing device according to the invention.

The Figure shown in the drawing shows a speech filter 1 in which the n input signals $S_n(M+S)$ are filtered, the speech signals $S_n(S)$ only being present at the output. The music signals $S_n(M)$ are obtained from the input signals and the speech signals by differentiating means 2. In practice, the speech filter and the differentiating means together form separating means for substantially separating the speech signals from the music signals. Such separating means are known per se from Karaoke techniques and are based on the effect, for example, that speech is present in a certain frequency band or is distributed over the input channels with a fixed weighting or a weighting which changes with the movement of speakers.

5
10

15
-
20
25

30

5

10

15